

Item description

PREWHITE™ PP 22-50

Item ID

225002

White masterbatch

Suitable polymers:

PP

Applications:

Medical

PREWHITE™ PP 22-50 is a white PP masterbatch for polypropylene extrusion coating applications. Due to the overall balance of formulation, fast line speeds up to 300m/min, and low coating weights down to 10g/m² can be achieved.

According to FDA and BgVV regulations **PREWHITE™ PP 22-50** is approved for use in contact with foodstuff without limitations.

Filling the screw to maximum and using maximum safe torque and melt pressure is recommended for optimal cleaning results.

Processing temperature 100 – 200 °C. Overheating may cause thermal degradation of the compound and the formation of fumes.

The maximum used dosage 30 is % and pre-drying e.g., 3 hours at 90 °C is recommended when dosed over 25 %.

Physical properties

Appearance	Granule	
Carrier	PP	
Pigmentation	TiO ₂	50%
Color	White	

Material properties

Material properties	Unit	Standard	Value
Physical properties			
Specific gravity	g/cm ³		1.5
Light fastness (very good)			8
Temperature stability	°C		<300
Moisture content (max when produced)	%		>0.15

Packaging

PREWHITE™ PE 22-50 are supplied in granule form, packed in 25 kg polyethylene valve bags (1250 kg) on one-way pallet. The product can be stored up to three years in normal storing conditions. Packages should be stored indoors and protected from sunlight and significant temperature changes. Shelf life is three (3) years when stored in above mentioned conditions in its original package.

The information in this datasheet represents typical values obtained by us and shall not be regarded as a product specification. The right to make any changes to the content and appearance of this document is reserved by Premix Oy. We condition that the product will be inspected and qualified by the customer for their process to meet the specific requirements set by application, processing equipment and the end product. The user of this product is held responsible for the evaluation of this product's suitability concerning applied legislation and possible patent infringements. We do not intentionally add or incorporate hazardous substances in our production.

Contact our technical sales:

www.premixgroup.com